



iSPAN[®] 3676 AdvancedMC[™] ATM OC-3/STM-1 Network Interface Card

Multiprotocol interworking technology for network migration

FEATURES

Single or Dual OC-3/STM-1 interfaces via SFP optics

Multimode/Single-mode fiber

Support for ATM AAL5 and AALO Adaptation Layers

Consistent Bit Rate (CBR), Variable Bit Rate (VBR) and Unspecified Bit Rate (UBR) services implemented in the hardware

OAM status notification

Classical IP (CLIP) support for Solaris and Linux

Automatic Protection Switching (APS) to ensure system availability for single port configuration

Performance at wire speed for AAL5 for active ports

- Assuming average packet size of 512 bytes

Provisioning support for up to 32k VCs with up to 4K simultaneously active using full duplex ports

Designed for ATCA platforms

Single width, Mid-size PICMG[™] AMC.0 R2.0 compliant

PCI-Express x1 (AMC.1) interface to the carrier

Mindspeed[™] CN8236 155 Mbps ATM SAR

Mindspeed[™] CX28250 PHY

Software Support

- Solaris
- Linux

APPLICATIONS

Access Equipment (e.g. DSLAM, DLC)

Signaling Gateways

ATM Signaling Monitors

Routers/Switches

Video Conferencing

Test Equipment

High Performance

Designed especially for high-availability, high-bandwidth access applications, the iSPAN 3676 provides ATM connectivity at 155 Mbps.

Reliable ATM Connectivity

Today's networks require scalable, high-performance platforms with the flexibility to allow network capacity to keep pace with customer's demands. The iSPAN 3676 controller meets the needs of a variety of applications, including IP switching and routing, internet connections and other applications that require the Quality of Service (QoS) guarantees provided by ATM.

Cost Effective

The competitive price of the iSPAN 3676 makes it the best 155Mbps value in the industry.



iSPAN 3676 ATM Network Interface Card

Hardware

The iSPAN 3676 AdvancedMC OC-3/STM-1 Network Interface Card is designed around the Mindspeed CN8236 ATM SAR and the Mindspeed CX28250 framer.

ATM SAR Engine

- Mindspeed CN8236 ATM SAR and Traffic Manager
- 4 MB SRAM per SAR device

PCI-Express Bridge

- PLX Technology PEX8111: PCIe x1 to PCI 32-bit/33 MHz bridge

OC-3/STM-1 Line Interfaces

- One or two, active, OC-3/STM-1 ports
 - Dual port configuration has a cumulative throughput of 200Mbps
- 1+1 APS support for OC-3/STM-1 for single port configuration
- Line transceivers in interchangeable SFP modules for maximum configurability

Telecom Clock Management

The 3676 utilizes clocks TCLKA, TCLKB, and FCLKA, as stated in the AMC.0 R2.0 specification.

Software

The 3676 is available with a kit for board & software development in Linux[®] and Solaris[®] environments. Included in this kit is the iSAR Application Programming Interface (API), providing a seamless and consistent interface between the 3676 and the operating system. The Interphase-developed API and software layers enable application development without the need to be involved in low layer ATM driver development. The Automatic Protection Switching (APS) feature is hardware supported, enabling maximum uptime, reliability and network resiliency with software notification and PHY modification support. The iSAR API is backwards compatible with other OC3/STM-1 Interphase NICs: iSPAN 4576 and iSPAN 5576 products.

Interphase Customer Service and Support

All Interphase products are backed by Support programs designed to deliver maximized uptime for our customers worldwide. Included are standard and extended product warranty packages, standard and enhanced “7x24” live technical assistance, and free Web-based online support for the life of the product, including technical notes, downloadable driver enhancements, and information on new product releases. Interphase Customer Support ensures investment protection for your networking applications.

Technical Specifications

Architecture

SAR Engine	Mindspeed CN8236
RAM Memory	4 MB SRAM
Framer/LIU	Mindspeed CX28250
AMC Connectivity	AMC.1 (PCI-Express x1)

Mechanical

Form Factor	AdvancedMC single-width mid height
Length	180.6 mm (7.11 in.)
Width	73.5 mm (2.89 in.)

Operating Environment

Power Consumption	13.6 W @ 12 V, 0.2 W @ 3.3 V
Temperature	0 to 55 °C (32 to 131 °F)
Storage Range	–40 to 80 °C (–40 to 176 °F)
Relative Humidity	10% to 95% non-condensing
Altitude	0 to 15,000 ft



Corporate Headquarters

2901 N. Dallas Parkway
Plano, Texas 75093
1-800-FASTNET
Phone: + 1.214.654.5000
Fax: + 1.214.654.5500

About Interphase Corporation

Interphase Corporation (NASDAQ: INPH) delivers solutions for LTE and WiMAX, interworking gateways, packet processing, network connectivity, and security for key applications for the communications and enterprise markets. The company also offers a comprehensive portfolio of desktop virtualization solutions. Founded in 1974, Interphase provides expert engineering design and electronics manufacturing services, in addition to its commercial-off-the-shelf (COTS) product portfolio. Interphase is headquartered in Plano, Texas, with sales offices in the United States and Europe. Clients include Alcatel-Lucent, Emerson Network Power, Fujitsu Ltd., Genband, Hewlett Packard, ip.access, Samsung, and Sun Microsystems.